

SERVICE BULLETIN SEC. VIII, DIV. A

NO.18

SERVICE BULLETIN 18 ISSUED NOVEMBER, 1963

MEWON

MICRO SEAL FOAM

AIR CLEANERS

•	POSITIVE SEAL	- Seals dirt out, Power in. No by passing of Element. No distortion of Element.
•	GREATER CAPACITY	- 3 times any previous Cleaner.
•	LONGER SERVICE LIFE	Pre-Treated for positive dirt filtration. Up to 50 hours under normal conditions.
		ei,
•	POSITIVE ENGINE PROTECTION	Engine will stop when replacement of Filter Element is required.
•	ONE PIECE ELEMENT	Foam and Seal molded in one piece.
٠	INTERCHANGEABILITY	Cleaner and Element adaptable to older units.
•	ALL POSITION AIR CLEANER	Can be used in any position making for greater adaptability.

MICRO SEAL FOAM AIR CLEANER

Clinton Engines Corporation has developed a new Air Cleaner Element using the foam type cleaner with a positive seal molded into one piece. This will eliminate any dirt by-passing the Filter. At the same time the design has been changed to use four (4) sides of the Element rather than one side as previously, giving three (3) times the capacity. The new positive seal on the element not only seals the dirt out, but acts as a wiper when the Element is removed from the container. The more dirt in the element the more positive the seal.


The new Mi Cro Seal Foam Air Cleaner is so positive in its action that when the Air Cleaner becomes clogged and before dirt will enter the engine, it will flood out the engine, thus giving positive protection to the engine.

Continued test under varying conditions in actual field test have proven that under normal conditions this Cleaner will operate for 50 hours before requiring replacement or reclaiming. It is our recommendation that the Air Cleaner Element be replaced due to special pre-treat ment of the Element at the factory. (Without this pre-treatment the efficiency of the Element is greatly reduced.)

The Element of the Mi Cro Seal Foam Cleaner is designed to interchange with many older units. (See chart on following page.) Also, complete Mi Cro Seal Foam Cleaners can be adapted to older model engines.

The Cleaner itself is designed to be used in any position allowing for adaptation to various model engines.

MICRO SEAL FOAMAIR CLEANER



Air Cleaner Ass'y 2-172-500 interchanges with the following Air Cleaner Assemblies.


4546-A ----- 2-9-500 4557-A ----- 2-11-500 4512-A ----- 2-2-500 6215-A ----- 2-6-500

MICRO SEAL FOAMAIR CLEANER

FOR VERTICAL SHAFT

ALUMINUM & CAST IRON

ENGINE









2_	1	77	- 5	nn	

2-139

2-175-990

45-337

2-177-500				
CAN BE USED IN PLACE OF				
AIR CLEANER ASS'Y				
00454 (440 ABE)				

92101 (149-477)

92103 (149-479)

USED ON	ENGINE
MODEL	NO.

401-0000-000

405-0000-000

407-0002-000

411-0002-000 415-0002-000 GASKET

92098 (94 - -458)

92098

(94 - 458)

92098

(94 - 458)

5812 (258-131)

92098 (94-458) 304-562

Washer 5812 (258-131)

HARDWARE

Screw 5812 (258-131)

304-562

Washer 5812 (258-131)


Screw


MICRO SEAL FOAMAIR CLEANER


FOR HORIZONTAL SHAFT

ALUMINUM & CAST IRON

ENGINE







2-178-500 CAN BE USED IN PLACE OF AIR CLEANER ASS'Y

2-157-500


USED ON ENGINE MODEL NO.	GASKET
400-0100-000	94-516
404-0100-000	94-516
406-0100-000	94-516
426-0100-000	94-516

HARDWARE 5677 (258-105) Screw 5677 (258-105) Screw 5677 (258-105) Screw 5677 (258-105) Screw

MICRO SEAL FOAMAIR CLEANER

FOR TILLER

&



CAN	2-169-500 BE USED IN PLACE OF AIR CLEANER ASS'Y	USED ON ENGINE MODEL NO.	GASKET	HARDWARE
	92101 (149-477)	401-0000-130	94-458	258-971 Screw
				304-614 Spacer
	2-157-500	404-0100-130	94-458	258-971 Screw
				91811 (900-340) Adapter
	2-177-500	407-0002-130	94-458	258-971 Screw
				304-614 Spacer
		412-0000-130	94-458	5812 (258-131) Screw
		415-0002-130	94-458	258-971 Screw 304-614 Spacer
		494-0101-130	94-458	5812 (258-131) Screw
		498-0301-130	94-458	5812 (258-131) Screw
	92102 (149-478)	499-0000-130	94-458	258-971 Screw
				304-614 Spacer


MICRO SEAL FOAMAIR CLEANER

FOR


HORIZONTAL & VERTICAL SHAFT



2-204-500



2-180



2-171



45-391

2-204-500 CAN BE USED IN PLACE OF AIR CLEANER ASS'Y

149-540

USED ON ENGINE MODEL NO.

500-0100-000

GASKET 94-13 HARDWARE 258-974 Screw

501-0001-000

94-13

258-974 Screw